

FlexWall® FW155/1-(MS)

Volumetric and gravimetric

General Information



The FlexWall® [FW155/1](#) feeder is ideal for free flowing bulk ingredients. The feeder has the following main components: a stainless steel rectangular housing, flexible polyurethane trough with a large trough cross-section, feed screw and screw tube, 3 phase AC motor and an extension hopper with volumes of 600 dm³ (21.19 cuft) or 1000 dm³ (35.31 cuft).

The shape of the trough provide a consistent screw filling and mass flow without ingredient deterioration.

Screw removal of the [FW155/1](#) is from the front only.

The FlexWall® is easily disassembled for wet or dry cleaning as the polyurethane trough that is attached to the housing is easily removed.

The [weighing system MS](#) is available as gravimetric version with four high-resolution load cells with advanced filtering technology.

The unit conforms to CE directives.



Model Specification

Screw drive	fixed
Drive power	1.5 kW (2.01 HP)
Screw speed	142 min ⁻¹
Massage paddles	no



Control Modules

Control and speed modules are offered either mounted onto the feeder ([Congrav® CM-E](#)) or are available for mounting in a separate control panel ([Congrav® CB-E](#) or [Congrav® CB-S](#)).

Controls can communicate directly to most host/ PLC systems or to Brabender Technologie Congrav® Operator Interfaces.



FlexWall® FW155/1-(MS)

Volumetric and gravimetric



Technical Drawings and Dimensions

	volumetric feeders	gravimetric feeders	
		Control module CB	Control module CM
600 dm ³ (21.19 cuft) Hopper	FW155/1-600	DDW-MS-FW155/1-600	DDW-MS-FW155/1-600 CM
1000 dm ³ (35.31 cuft) Hopper	FW155/1-1000	DDW-MS-FW155/1-1000	DDW-MS-FW155/1-1000 CM

Available Screw Sizes and Feed Rates

Screw type	Designation Ø / p [mm]	Tube designation	Tube dia. [mm]	Max. speed [min ⁻¹]	Max. feed rate * [dm ³ /h]	Max. feed rate * [cuft/h]
Spiral Screw (S)	S 103/105	1091	114.3x2.6	142 / 100Hz	7185	253.7
	S 120/120	1270	133.0x3.0	142 / 100Hz	11245	397.1
	S 155/100	1631	168.3x2.6	142 / 100Hz	15503	547.5
	S 155/165	1631	168.3x2.6	142 / 100Hz	25925	915.6
Spiral Screw (S) for granules	S 103/105	1270	133.0x3.0	142 / 100Hz	8870	313.2
	S 120/120	1631	168.3x2.6	142 / 100Hz	15530	548.5
Blade Screw (B)	B 103/105	1091	114.3x2.6	142 / 100Hz	6600	233.1
	B 120/120	1270	133.0x3.0	142 / 100Hz	10530	371.9
	B 155/100	1631	168.3x2.6	142 / 100Hz	14975	528.9
	B 155/165	1631	168.3x2.6	142 / 100Hz	24985	882.4

* Theoretical values at 100% screw filling level and motor speed. Depending on the flow characteristics the screw filling level may decrease to 50%.
Further limitations have to be considered for gravimetric feeding, as max. speed should be reduced to allow for bulk density variations.
[How to read the table of screws](#)



FlexWall®

FW155/1-(MS)

Volumetric and gravimetric

Technical Specification

Ambient temperature:	0°C to +45°C (32°F to 113°F)
Humidity of the air:	up to 85% without condensation
max. vacuum/pressure:	3 hPa (3 mbar) (1.2 inches of water)
Ingredient temperature:	0°C to +50°C (32°F to 122°F)
max. bulk density (volumetric):	1.5 kg/dm ³ * (94 lb/cuft)
max. bulk density (gravimetric):	1.5 kg/dm ³ (94 lb/cuft) with hopper 600dm ³ (21.19 cuft) 1.5 kg/dm ³ (94 lb/cuft) with hopper 1000 dm ³ (35.31 cuft)
Flexible screw trough:	polyurethane, food-proof acc. to LMBG*
Housing, extension hopper, hopper lid:	1.4301 (304 SS) 1.4571 (316 SS), 1.4301 (304 SS) or polyurethane, food-proof acc. to LMBG*
Screws, screw tubes, outlets:	LMBG*
Non-contact components:	Aluminum, plated or painted steel (RAL 7035)
Extension hopper 600 dm³ (21.19 cuft) or 1000 dm³ (35.31 cuft) :	Hopper lid for inlet and vent connections
Screw drive:	1.5 kW (2.04 HP), IP66; ISO class F; TEFC; frequency-controlled
Power supply:	AC 230/400 V (110VAC/460VAC)- 50Hz**
Net weighing range MS:	1780 kg (3924 lb) with hopper 600 dm ³ (21.19 cuft)
Net weighing range MS:	1730 kg (3814 lb) with hopper 1000 dm ³ (35.31 cuft)

* Optionally available: conductive or chemically resistant FDA approval polyurethane
 ** Three-phase motors are designed for a power supply of: 230/400 V - 50 Hz, and for the operation in TT networks, TN networks or networks with earthed neutral. For different networks adaptation measures are necessary.

Options and Accessories

- Flexible [inlet and vent connections](#)
- Flexible [outlet connections](#)
- Interchangeable screws and screw tubes
- [BagDumper](#) (for manual refilling)
- [DESTACO clamp fasteners](#) with and without safety switch
- Versions for higher or lower temperatures than standard
- [Explosion-proof versions](#) as per directive 2014/34/EU (ATEX) or NFPA
- Vertical outlet with [quick release](#)
- [Maintenance disconnect box](#)
- [Filter bag](#) or [JetFilter](#) for vent pipe
- [Turntable](#) or [cart mounting](#)
- [Pressure compensation for the outlet](#) and/or [feeder hopper](#)
- Cleaning and refill systems upon request

